

Datalogging Thermometer

code: R0110E



Temperature datalogger is designed for record of temperature. Values are stored to a non volatile electronic memory. Data transfer to the personal computer for further analysis is performed via USB, RS232, GSM or Ethernet interface by means of a proper adapter.

The device **includes Traceable calibration certificate** with declared metrological traceability of etalons is based

on requirements of **EN ISO/IEC 17025 standard**.

For communication with the PC must be from Optional accessories ordered [USB adapter](#) or [COM adapter](#) or [start/stop magnet](#) if is needed to control logging the other way than directly from computer.

Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +70 °C
Accuracy	$\pm 0.6^{\circ}\text{C}$ (-30 to +30 °C); $\pm 0.8^{\circ}\text{C}$ (+30 to +70 °C)
Resolution	0.1 °C
GENERAL TECHNICAL DATA	
Operating temperature	-40 to +80 °C
Channels	internal temperature sensor
Memory	32,000 values (non-cyclic record)
Recording interval	adjustable from 10 s to 24 h
Display and alarm refresh	each 10 s
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	lithium battery 3.6 V; size AA
Battery life	7 years
Protection class	IP67
Dimensions	93 x 64 x 27 mm
Weight (including batteries)	approx. 100 g
Warranty	3 years