

## Temperature probe Pt1000TG68/M, MiniDin connector, cable 1 meter

code: SN251M

Multi-purpose watertight IP68 probe -50 to +200°C.

Stainless steel 17241 with silicone cable of specified length. Diameter 6mm, length 60mm. With MiniDIN connector.



Time response t0,50.5m.s-1)

The sensors meet the IP68 ingress protection requirements according to the EN 60 529 standard. They can be immersed permanently up to depth of 5m.

### Technical data

|                         |                                            |
|-------------------------|--------------------------------------------|
| TEMPERATURE SENSOR      |                                            |
| Measuring range         | -50 to +200 °C                             |
| Accuracy                | $\pm (0.15 + 0.002 t)$ at °C               |
| Accuracy class          | A                                          |
| Time response           | t0.5 <12 s (in flowing water at > 0.2 m/s) |
| Type of sensing element | Pt1000                                     |
| Temperature coefficient | 3850 ppm / °C                              |
| GENERAL TECHNICAL DATA  |                                            |
| Wire connection         | 2-wire connection                          |
| Material of the case    | stainless steel DIN 1.4404                 |
| Dimensions of the case  | length 60 mm; <br>diameter 6 ± 0.1 mm      |
| Lead-in cable           | silicone shielded                          |
| Length of lead-in cable | 1 meter                                    |
| Connector               | MiniDin                                    |
| IP protection           | IP68                                       |
| Warranty                | 30 months                                  |