

## Web Sensor - remote thermometer hygrometer barometer with Ethernet interface, cable 2 meters

code: T7511-2



Ambient temperature, relative humidity, atmospheric pressure t-line Web sensor. Remote alarm.

Web Sensor with relative humidity and temperature probe on the cable. Built-in atmospheric pressure sensor.

High precision capacitive polymer sensor ensures excellent long term calibration stability and ultimate accuracy. Dual line LCD is an advantage. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy.

The device is supplied with T+RH probe with 2 meters cable.

### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

**With a newly purchased WebSensor with Ethernet communication, you receive 3 months of [COMET Cloud](#). for free; a full year of operation in [COMET Cloud](#). then requires [1 credit](#).**

### Technical data

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| TEMPERATURE SENSOR                 |                                                      |
| Measuring range                    | -30 to +105 °C                                       |
| Accuracy                           | ±0.4 °C                                              |
| Resolution                         | 0.1 °C                                               |
| HUMIDITY SENSOR                    |                                                      |
| Measuring range                    | 0 to 100 % RH                                        |
| Accuracy                           | ±2.5 % RH from 5 to 95 % at 23 °C                    |
| Resolution                         | 0.1% RH                                              |
| DEW POINT                          |                                                      |
| Measuring range                    | -60 to +80 °C                                        |
| Accuracy                           | ±1.5 °C at ambient temperature T <25 °C and RH >30 % |
| Resolution                         | 0.1 °C                                               |
| ATMOSPHERIC PRESSURE SENSOR SENSOR |                                                      |
| Measuring range                    | 600 to 1100 hPa                                      |
| Accuracy                           | ±1.3 hPa at 23 °C from 800 to 1100 hPa               |
| Resolution                         | 0.1 hPa                                              |
| GENERAL TECHNICAL DATA             |                                                      |
| Operating temperature              | -30 to +80 °C                                        |

|                                                   |                                                                                  |
|---------------------------------------------------|----------------------------------------------------------------------------------|
| Channels                                          | internal atmospheric pressure sensor, 1x connectable temperature+humidity probe  |
| Counted values                                    | dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy |
| Output                                            | Ethernet                                                                         |
| Range of humidity sensor temperature compensation | all temperature range                                                            |
| Measuring interval                                | 2 s                                                                              |
| Available temperature units                       | degrees Celsius, degrees Fahrenheit                                              |
| Available pressure units                          | hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2                                   |
| Communication protocol                            | WWW, ModbusTCP, SNMPv1, SOAP, XML                                                |
| Alarm protocols                                   | E-mail, SNMP Trap, Syslog                                                        |
| Power                                             | 9-30 Vdc                                                                         |
| Protection class                                  | IP30 electronics; IP40 sensors                                                   |
| Dimensions                                        | 88,5 x 147,5 x 39,5 mm; stem length 75 mm                                        |
| External probe cable length                       | 2 meters                                                                         |
| Weight                                            | approx. 155 g                                                                    |
| Warranty                                          | 3 years                                                                          |